

**5** PLUS

SLIMTECH EXTENSION

**LEA**

CERAMICHE

UNO  
SPESSORE  
PER  
OGNI  
SITUAZIONE

A THICKNESS FOR ALL SITUATIONS

UN  
FORMATO  
PER  
OGNI  
PROGETTO


A FORMAT FOR ALL PROJECTS

UNA  
NUOVA  
FONTE DI  
ISPIRAZIONE

A NEW SOURCE OF INSPIRATION

UNA  
COLLEZIONE  
SENZA  
LIMITI

A COLLECTION WITHOUT LIMITS



La superficie ad effetto pietra di Waterfall diventa Slimtech. L'inserimento del gres laminato potenzia la collezione amplificando l'effetto mutevole e materico della pietra. La creatività, ispirata dalle nuove possibilità di posa, si apre a nuovi confini. Una perfetta sintesi di realismo naturale e tecnologia.

*The stone effect surface of Waterfall becomes Slimtech. The inclusion of laminated porcelain enhances the collection by amplifying the changeable and material effect of the stone. Creativity, inspired by the new laying possibilities, opens new boundaries. A perfect synthesis of natural realism and technology.*

WATERFALL

## FORMATI / SIZES

NAT

**SPESSORE / THICKNESS 5,5 mm**

100x300cm / 39"x118"  
slimtech 5plus

100x100cm / 39"x39"  
slimtech 5plus

50x100cm / 19 1/2"x39"  
slimtech 5plus

**NEW**

## COLORI / COLORS



## FORMATI / SIZES

NAT / LAPP / GRIP\*

**SPESSORE / THICKNESS 10,5 mm**

30x60cm / 12"x24" rett

60x60cm / 24"x24" rett

90x90cm / 36"x36" rett

45x90cm / 18"x36" rett

60x120cm / 24"x48" rett

**SPESSORE / THICKNESS 20 mm**

**SYSTEM L2**  
45x90cm / 18"x36"  
± 20mm

**SYSTEM L2**  
60x60cm / 24"x24"  
± 20mm

\* solo 60x60cm / 24"x24"  
only 60x60cm / 24"x24"

## COLORI / COLORS



## FORMATI SPECIALI SPECIAL SIZES

**gramma 72**  
49,8x16,9cm / 19 1/2"x6 5/8" rett  
nat

**gramma 66 dx**  
39,2x19,5cm / 15 3/8"x7 5/8" rett  
nat

**gramma 16 dx**  
19,5x9,7cm / 7 5/8"x3 3/4" rett  
nat

**gramma 66 sx**  
39,2x19,5cm / 15 3/8"x7 5/8" rett  
nat

**gramma 16 sx**  
19,5x9,7cm / 7 5/8"x3 3/4" rett  
nat

## MOSAICI / MOSAICS

**MURETTO**  
30x60 cm / 12"x24" rett  
nat / lapp

**BRICK**  
30x60 cm / 12"x24" rett  
nat / lapp

**MURETTO 3D**  
30x60 cm / 12"x24" rett  
nat / lapp

**MOSAICO 36**  
30x30 cm / 12"x12" rett  
nat / lapp

# WATERFALL

FONDI PLAIN TILES



			Ivory flow	Silver flow	Gray flow	Dark flow
<b>50x100cm</b> 19 <sup>1/2</sup> "x39"	Slimtech 5plus	NAT	LS9WF20	LS9WF30	LS9WF10	LS9WF00
<b>100x100cm</b> 39"x39"	Slimtech 5plus	NAT	LSCWF20	LSCWF30	LSCWF10	LSCWF00
<b>100x300cm*</b> 39"x118"	Slimtech 5plus	NAT	LSAWF20	LSAWF30	LSAWF10	LSAWF00

\* Per ordini inferiori alle 5 lastre sarà addebitato il costo del pallet a Euro 80,00 netto. / The cost of the pallet, Euro 80,00 net, will be charged for orders less than 5 slabs.

FONDI PLAIN TILES

				Ivory flow	Silver flow	Gray flow	Dark flow
<b>30x60cm</b> 12"x24"	rett	10,5 mm	NAT	LGWVFN2	LGWVFN3	LGWVFN1	LGWVFN0
			LAPP	LGWVFX2	LGWVFX3	LGWVFX1	LGWVFX0
			GRIP	-	-	-	-
<b>60x60cm</b> 24"x24"	rett	10,5 mm	NAT	LGWWFN2	LGWWFN3	LGWWFN1	LGWWFN0
			LAPP	LGWWFX2	LGWWFX3	LGWWFX1	LGWWFX0
			GRIP	LGWWF20	LGWWF30	LGWWF10	LGWWF00
<b>45x90cm</b> 18"x36"	rett	10,5 mm	NAT	LGGWFN2	LGGWFN3	LGGWFN1	LGGWFN0
			LAPP	LGGWFX2	LGGWFX3	LGGWFX1	LGGWFX0
			GRIP	-	-	-	-
<b>90x90cm</b> 36"x36"	rett	10,5 mm	NAT	LG9WF20	LG9WF30	LG9WF10	LG9WF00
			LAPP	LG9WF2	LG9WF3	LG9WF1	LG9WF0
			GRIP	-	-	-	-
<b>60x120cm</b> 24"x48"	rett	10,5 mm	NAT	LGXWF20	LGXWF30	LGXWF10	LGXWF00
			LAPP	LGXWF2	LGXWF3	LGXWF1	LGXWF0
			GRIP	-	-	-	-
<b>Gamma 72</b> <b>49,8x16,9cm</b> 19 <sup>1/2</sup> "x6 <sup>5/8</sup> "	rett	10,5 mm	NAT	LGZWF2	LGZWF3	LGZWF1	LGZWF0
<b>Gamma 66 SX</b> <b>39,2x19,5cm</b> 15 <sup>3/8</sup> "x7 <sup>5/8</sup> "	rett	10,5 mm	NAT	LGZWF2	LGZWF3	LGZWF1	LGZWF0
<b>Gamma 66 DX</b> <b>39,2x19,5cm</b> 15 <sup>3/8</sup> "x7 <sup>5/8</sup> "	rett	10,5 mm	NAT	LGZWF2	LGZWF3	LGZWF1	LGZWF0
<b>Gamma 16 SX</b> <b>19,5x9,7cm</b> 7 <sup>5/8</sup> "x3 <sup>3/4</sup> "	rett	10,5 mm	NAT	LG0WFS2	LG0WFS3	LG0WFS1	LG0WFS0
<b>Gamma 16 DX</b> <b>19,5x9,7cm</b> 7 <sup>5/8</sup> "x3 <sup>3/4</sup> "	rett	10,5 mm	NAT	LG0WFD2	LG0WFD3	LG0WFD1	LG0WFD0
<b>45x90cm</b> 18"x36"	rett	20 mm SYSTEM L2	NAT	LGGK220	LGGK230	LGGK210	LGGK200
<b>60x60cm</b> 24"x24"	rett	20 mm SYSTEM L2	NAT	LGWK2W5	LGWWF36	LGWK2W3	LGWK2W1

PEZZI SPECIALI TRIMS

			Ivory flow	Silver flow	Gray flow	Dark flow
 <b>battiscopa</b> 10x60cm / 4"x24" rett	LAPP	LGBWFL2	LGBWFL3	LGBWFL1	LGBWFL0	
	NAT	LGBWFN2	LGBWFN3	LGBWFN1	LGBWFN0	
 <b>gradino plus*</b> 35x120cm / 13 <sup>3/4</sup> "x48" rett	LAPP	LG8WF70	LG8WF80	LG8WF60	LG8WF50	
	NAT	LG8WF20	LG8WF30	LG8WF10	LG8WF00	
 <b>angolo dx gradino plus*</b> 35x120cm / 13 <sup>3/4</sup> "x48" rett	LAPP	LG8WF71	LG8WF81	LG8WF61	LG8WF51	
	NAT	LG8WF21	LG8WF31	LG8WF11	LG8WF01	
 <b>angolo sx gradino plus*</b> 35x120cm / 13 <sup>3/4</sup> "x48" rett	LAPP	LG8WF72	LG8WF82	LG8WF62	LG8WF52	
	NAT	LG8WF22	LG8WF32	LG8WF12	LG8WF02	
 <b>gradino plus*</b> 35x60cm / 13 <sup>3/4</sup> "x24" rett	GRIP	LG2WF20	LG2WF30	LG2WF10	LG2WF00	
	GRIP	LG2WF21	LG2WF31	LG2WF11	LG2WF01	

\* Su richiesta. Per maggiori informazioni circa quantità minime e tempi di consegna rivolgersi all'ufficio commerciale. / Upon request. For more information about minimum quantities and delivery times please contact the sales department.

MOSAICI MOSAICS

			Ivory flow	Silver flow	Gray flow	Dark flow
<b>Muretto</b> <b>30x60cm</b> 12"x24"	LAPP	LGBWFL2	LGBWFL3	LGBWFL1	LGBWFL0	
	NAT	LGBWFN2	LGBWFN3	LGBWFN1	LGBWFN0	
<b>Brick</b> <b>30x60cm</b> 12"x24"	LAPP	LG8WF70	LG8WF80	LG8WF60	LG8WF50	
	NAT	LG8WF20	LG8WF30	LG8WF10	LG8WF00	
<b>Muretto 3D</b> <b>30x60cm</b> 12"x24"	LAPP	LG8WF71	LG8WF81	LG8WF61	LG8WF51	
	NAT	LG8WF21	LG8WF31	LG8WF11	LG8WF01	
<b>Mosaico 36</b> <b>30x30cm</b> 12"x12"	LAPP	LG8WF72	LG8WF82	LG8WF62	LG8WF52	
	NAT	LG8WF22	LG8WF32	LG8WF12	LG8WF02	

# CARATTERISTICHE TECNICHE SLIMTECH 5PLUS

TECHNICAL CHARACTERISTICS SLIMTECH 5PLUS

lastra + fibra di vetro / slab + fiberglass

gres porcellanato laminato UGL / laminated porcelain stoneware UGL

conforme / according to: ISO 13006 G (Gruppo/Group Bla) - EN 14411 G (Gruppo/Group Bla), ANSI A137.3



		metodo di prova test method	requisiti prescritti required values	valori medi average values
	<b>assorbimento d'acqua</b> water absorption	ISO 10545-3 ASTM C373	≤ 0,5%	0,1%(*)
	<b>resistenza alla flessione</b> modulus of rupture	ISO 10545-4 ASTM C1505	≥ 35 N/mm <sup>2</sup> ≥ 6000 PSI	50 N/mm <sup>2</sup> ≥ 6000 PSI
	<b>resistenza all'abrasione profonda</b> résistance to deep abrasion	ISO 10545-6 ASTM C1243	≤ 175 mm <sup>3</sup>	CONFORME CONFORMS
	<b>dilatazione termica lineare</b> linear thermal expansion	ISO 10545-8 ASTM C372	requisito non previsto no provision	$\alpha \leq 7 \times 10^{-6} \text{ } ^\circ\text{C}^{-1}$ $\alpha \leq 4.4 \times 10^{-6} \text{ } ^\circ\text{F}^{-1} / \alpha \leq 8 \times 10^{-6} \text{ } ^\circ\text{C}^{-1}$
	<b>resistenza alle macchie</b> stain resistance	ISO 10545-14 ASTM C1378	Classe / Class 3 Min. as indicated by manufacturer	5 RESISTENTE / RESISTANT Class A RESISTANT
	<b>resistenza all'attacco chimico (**)</b> chemical resistance (**)	ISO 10545-13 ASTM C650	come indicato dal produttore as indicated by manufacturer	ULA - UHA RESISTENTE / RESISTANT Class A RESISTANT
	<b>resistenza al gelo</b> frost resistance	ISO 10545-12 ASTM C1026	nessuna alterazione / no alteration as indicated by manufacturer	RESISTENTE / RESISTANT RESISTANT
	<b>resistenza allo scivolamento</b> slip resistance	DIN 51130 BCR-TORTUS ANSI A137.1	- - -	R10 $\mu > 0,40$ ≥ 0.42
	<b>reazione al fuoco</b> fire reaction flame spread	EN 13823 EN 9239-1 ASTM E84	Reg. 305/2011, Dec. 2000/147/CE, UNI EN 13501-1 no provision	Classe / Class A2-s1,d0 (wall) Classe / Class A2fl-s1 (floor) Class A
	<b>robinson floor tester</b>	ASTM C627	come indicato dal produttore as indicated by manufacturer	≥ 12 cycles Heavy Commercial (over concrete)
	<b>conducibilità termica</b> thermal conductivity	EN 12524	-	$\lambda = 1,3 \text{ W/m}^\circ \text{ k} / 0.7 \text{ BTU/ft h}^\circ \text{ F}$
	<b>stonalizzazione</b> shade variation	ANSI A137.1	come indicato dal produttore as indicated by manufacturer	V3 VARIAZIONI MODERATE / MODERATE VARIATION

fuga minima consigliata: vedi Manuale Tecnico Slimtech / minimum suggested joint: refer to Slimtech Technical Manual

(\*) valore medio riferito al solo materiale ceramico / average value referred to ceramic material only

(\*\*) ad esclusione dell'acido fluoridrico e derivati / excluding hydrofluoric acid and its derivatives

per le caratteristiche tecniche del Gres Porcellanato consultare il catalogo di linea Waterfall / for the technical features of the Porcelain Stoneware refer to the catalogue of the Waterfall collection

**LEA**  
CERAMICHE

LEA CERAMICHE  
Via Cameazzo, 21  
41042 Fiorano Modenese  
Modena Italy

Tel +39 0536 837811  
Fax +39 0536 830326  
info@ceramichelea.it  
www.ceramichelea.com

SHOWROOM LEA CERAMICHE  
Via Durini, 3  
20122 Milano

Tel +39 02 76011406  
showroom\_milano@ceramichelea.it

LEA NORTH AMERICA, LLC  
800 Clanton Road, Suite N  
Charlotte, NC 28217

Tel +1 704 522 6300  
Fax +1 704 522 6080  
info@leausa.us  
www.leausa.us

Panariagroup Industrie Ceramiche  
S.p.A.